

09/035,136 (Grove et al.)

Attorney Docket Number 27916/128354

1. A foot flexion device for use by a patient, comprising at least one boot comprising

a calf member having a heel end and a knee end and constructed and arranged to support a calf portion of said patient's leg

a baseplate having a heel end and a toe end, wherein said calf [plate] member and said base plate are rigidly attached to one another at said heel ends,

a footplate having a footplate toe end and a footplate heel end, said footplate heel end being rotatably attached to said heel end of said baseplate so that said footplate may rotate with respect to said baseplate,

an inflatable bellows positioned between said baseplate and said footplate such that inflation of said bellows causes rotation of said footplate relative to said baseplate to effect flexion of said patient's foot when said foot is disposed on said footplate,

securing structure constructed and arranged to secure said patient's foot such that said footplate and foot move together,

a pump assembly for pumping fluid to said bellows to power movement of said footplate,

a controller operatively coupled to said pump assembly by at least one sensor constructed and arranged to sense and transmit a sensor signal from a muscle of said patient to said controller,

wherein said controller is constructed and arranged to receive said signal and pause said pumping when said signal indicates that said muscle is contracting spontaneously or irregularly, and

wherein said knee end of said calf member does not extend higher than the knee of said patient.

09/035,136 (Grove et al.)

Attorney Docket Number 27916/128354

33 34. A foot flexion device for use by a patient, comprising  
at least one boot comprising

a calf member having a heel end and a knee end and constructed  
and arranged to support a calf portion of said patient's leg

a baseplate having a heel end and a toe end, wherein said calf  
[plate] member and said base plate are rigidly attached to one another at  
said heel ends,

a footplate having a footplate toe end and a footplate heel end,  
said footplate heel end being rotatably attached to said heel end of said  
baseplate so that said footplate may rotate with respect to said baseplate,

an inflatable bellows positioned between said baseplate and said  
footplate such that inflation of said bellows causes rotation of said  
footplate relative to said baseplate to effect flexion of said patient's foot  
when said foot is disposed on said footplate,

securing structure constructed and arranged to secure said  
patient's foot such that said footplate and foot move together,

a pump assembly for pumping fluid to said bellows to power  
movement of said footplate,

a controller operatively coupled to said pump assembly by at least  
one switch constructed and arranged to be operable by an operator to  
send a signal to said controller,

wherein said controller is constructed and arranged to receive said  
signal and pause said pumping when said signal is received, and  
wherein said knee end of said calf member does not extend higher than  
the knee of said patient.